

(حجم)
Volume
10-45 m^3



[D] TYPE VERTICAL PULPER

پالپر نوع D برای آسیاب‌کردن خمیر کاغذ استفاده می‌شود. ساختار مخزن پالپر به شکل D است که باعث افزایش تماس بین خمیر و پروانه می‌شود؛ بنابراین زمان آسیاب کردن خمیر کوتاه‌تر می‌گردد. انتقال قدرت در آن به روش تسمه و پولی است. این دستگاه برای خمیرسازی AOCC ، LOCC و...، برای جدا کردن پلاستیک‌ها، یونولیت‌ها و سایر ناخالصی‌های سبک و سنگین از مخزن پالپر برای جلوگیری از انتقال زباله‌ها و ناخالصی‌ها به مراحل بعد و خرد شدن آنها استفاده می‌شود و باعث بالارفتن ظرفیت تولید و تمیزتر شدن خروجی می‌شود.

[**D**] type hydrapulper is used for continuously pulping waste paper. The pulper tank shape is a [**D**] structure, increasing contact between the rotor and pulp, so the pulping time is shorter. The power is transmitted by a pulley and belt system.
This equipment is used for pulping LOCC, OCC etc., removing the plastics, Styrofoam and other light and heavy impurities from the pulper tank as early as possible, to avoid them being chopped and flow through the screen plate, so the capacity is higher and the pulp is cleaner.

ITEM | TYPE	VLP10A	VLP15A	VLP20A	VLP25A	VLP30A	VLP35A	VLP40A	VLP45A
Volume (m^3) حجم	10	15	20	25	30	35	40	45
Capacity (t/d) ظرفیت تولید	20 ~ 40	40 ~ 120	80 ~ 150	100 ~ 180	120 ~ 200	150 ~ 250	200 ~ 300	250 ~400
Power (KW) توان	55 ~ 75	75 ~ 90	110 ~ 132	160	250	280	315	355
Consistency (%) غلظت	3 ~ 5							