(حجم)
Volume
10-45 m^3





HORIZONTAL PULPER

پالپر نوع افقی برای آسیاب کردن خمیر کاغذ استفاده می‌شود. ساختار مخزن پالپر افقی به شکلی است که سنگ و سایر ناخالصی‌های آخال به پروانه و مش پالپر برخورد نکرده و باعث افزایش عمر آن می‌گردد. انتقال قدرت در آن به روش تسمه و پولی است. این دستگاه برای خمیرسازی AOCC ، LOCC و...، برای جدا کردن پلاستیک‌ها، یونولیت‌ها و سایر ناخالصی‌های سبک و سنگین از مخزن پالپر برای جلوگیری از انتقال زباله‌ها و ناخالصی‌ها به مراحل بعد و خرد شدن آنها استفاده می‌شود و باعث بالارفتن ظرفیت تولید و تمیزتر شدن خروجی می‌شود.

The horizontal pulper is used for grinding pulp. The structure of the horizontal pulper tank is designed so that stones and other impurities do not come into contact with the rotor and the pulper screen, thereby increasing its lifespan. Power transmission is achieved through a belt and pulley system. This device is employed for pulping LOCC, AOCC, etc., to separate plastics, polystyrene, and other light and heavy impurities from the pulper tank, preventing the transfer of waste and impurities to subsequent stages and their further fragmentation. This results in increased production capacity and a cleaner output.

ITEM | TYPE	HLP10A	HLP15A	HLP20A	HLP25A	HLP30A	HLP35A	HLP40A	HLP45A
Volume (m^3) حجم	10	15	20	25	30	35	40	45
Capacity (t/d) ظرفیت تولید	20 ~ 40	40 ~ 120	80 ~ 150	100 ~ 180	120 ~ 200	150 ~ 250	200 ~ 300	250 ~400
Power (KW) توان	55 ~ 75	75 ~ 90	110 ~ 132	160	250	280	315	355
Consistency (%) غلظت	3 ~ 5							