FIBRIZER

سیستم شارژ و تخلیه پیوسته پالپرهای غلظت پایین:

این سیستم برای پیوسته کردن کارکرد پالپر غلظت پایین و در مواقعی غلظت بالا استفاده می‌شود که دستگاه جداکننده آشغال (فایبرایزر یا پوآر یا هیدروپورج) و درام اسکرین به مدار پالپر اضافه می‌شود. همچنین برای تکمیل فرآیند می‌توان راگر و گرپل را نیز به این سیستم اضافه نمود. در این سیستم رجکت سنگین توسط تله‌ها و رجکت سبک توسط درام اسکرین و راگر و گرپل از سیستم خارج می‌شود و نیازی به شست و شوی دستی پالپر توسط اپراتور نمی‌باشد.

Continuous Charging and Discharging System for Low-Consistency Pulpers:

This system is designed to ensure the continuous operation of low-consistency pulpers (and in some cases, high-consistency pulpers) by integrating a trash separator—such as a fiberizer, poar, or hydropurger—and a drum screen into the pulper circuit. Furthermore, to complete the process, a raker and a grepel can also be incorporated into this system. In this setup, heavy rejects are removed via traps, while light rejects are discharged through the drum screen, raker, and grepel, eliminating the need for manual pulper cleaning by the operator.

